



Rectangular Semi Rigid Aluminum Flexible Duct SM-140 R

This Class 0" Rectangular Semi-Rigid Aluminum Air Duct is constructed of a special aluminum alloy that prevents corrosion and metal fatigue. The machine fabrication produces a continuous lock seam that permits the duct to be pulled open, compressed, bent and re-bent without developing leakage. This duct will not delaminate or dry rot when heat aged. It can be installed with severe bends and in unlimited lengths while maintaining an unrestricted diameter. It is compressed to nearly 3 times its original length for convenient shipping and handling.

Product Range:

Standard Length	6 feet
-----------------	--------

Performance Data :

Maximum Velocity	5000 FPM
Temperature Range	-73°C to 224°C
Permeance	Near Zero

Feature Benefits of Semi Rigid Aluminum Flexible Duct SM-140 R

- Supplied in standard 10 feet length.
- Multi boxed Packing.
- Low costs on transport and logistic.
- Easy to Install
- No special tool required for cutting or fixing
- In case of a fire no toxic gases are emitted
- The products have been tested on fire resistance
- Lifetime durability.
- Premium quality at an affordable cost.

Application of Rectangular Semi Rigid Aluminum Duct SM-140 R

SM Aluminum Flexible Ducting can be used in a number of applications including: Heating Air Conditioning, Exhaust and Fresh Air Intakes Ideal for use in clothes dryer, Bathroom and Kitchen exhausts.